


管径称	適合配管径 (A)	ネジ径d	t × B	P				
				T20	T25	T30	T40	T50
8A	9.53	W3/8	1.6 × 25	57	67	77	97	117
10A	12.7	W3/8	1.6 × 25	60	70	80	100	120
15A	15.88	W3/8	1.6 × 25	63	73	83	103	123
19A	19.05	W3/8	1.6 × 25	66	76	86	106	126
20A	22.22	W3/8	1.6 × 25	69	79	89	109	129
	25.4	W3/8	1.6 × 25	73	83	93	113	133
25A	28.58	W3/8	1.6 × 25	76	86	96	116	136
	31.8	W3/8	1.6 × 25	79	89	99	119	139
32A	34.92	W3/8	1.6 × 25	82	92	102	122	142
	38.1	W3/8	1.6 × 25	85	95	105	125	145
40A	41.28	W3/8	1.6 × 25	89	99	109	129	149
	50.8	W3/8	1.6 × 25	98	108	118	138	158
50A	53.98	W3/8	1.6 × 25	101	111	121	141	161
	63.5	W3/8	2.3 × 25	112	122	132	152	172
65A	66.68	W3/8	2.3 × 25	115	125	135	155	175
80A	79.38	W3/8	2.3 × 25	128	138	148	168	188
100A	104.78	W3/8	2.3 × 25	153	163	173	193	213

承認	検図	名称			ウレタンCM		
		材質	SPHC	表面処理	電気亜鉛めっき	尺度	1:2
設計	製図	板厚	1.6t、2.3t	単重		角法	第三角法
		図番	10200040222			RevNo.	△ 3-1
		 <b>日栄インテック株式会社</b> 管材事業部				SHEET	A3