



管径称	適合配管径 (A)	t×B	d	P	L1	L2	T
15A	21.7	2.0×25	3/8	48	80	25	10.0
20A	27.2	2.0×25	3/8	54	90	30	10.0
25A	34.0	2.0×25	3/8	61	90	30	10.0
32A	42.7	2.0×25	3/8	69	105	40	10.0
40A	48.6	2.0×25	3/8	75	105	40	10.0
50A	60.5	2.0×25	3/8	87	120	50	10.0
65A	76.3	2.0×25	3/8	103	135	50	10.0
80A	89.1	2.0×25	3/8	116	145	80	10.0
100A	114.3	2.0×25	3/8	141	170	80	10.0
125A	139.8	2.0×32	1/2	167	200	100	10.0
150A	165.2	2.0×32	1/2	192	225	100	10.0

サイズ	d	ネジ部	C
15A~25A	3/8	20	25
32A~50A	3/8	30	25
65A~100A	3/8	35	25
125A~150A	3/8	40	25
125A~150A	1/2	50	30

承認	検図	名称 ステンレス防振UバンドP付		
		材質 SUS304	表面処理 HL	尺度 1:1
設計	製図	板厚	単重	角法 第三角法
		図番 10220010954		RevNo. 0-2
日栄インテック株式会社 管材事業部				SHEET A3